

KP High Pressure - Pump Performance Chart

Model	SPM @1750 RPM	Capacity @ 60 Hz		Pressure		Connection		Motor
		GPH	LPH	PSI	BAR	NPT/BPT	Flange	
KPL-10	20	0.14	0.5	1500	100	1/2"	1/2"	1/2 Hp
	31	0.21	0.8	1500	100	1/2"	1/2"	1/2 Hp
	46	0.31	1.2	1500	100	1/2"	1/2"	1/2 Hp
	60	0.41	1.6	1500	100	1/2"	1/2"	1/2 Hp
KP-10	20	0.3	1.1	1500	100	1/2"	1/2"	1/2 Hp
	31	0.4	1.7	1500	100	1/2"	1/2"	1/2 Hp
	46	0.7	2.5	1500	100	1/2"	1/2"	1/2 Hp
	60	0.9	3.3	1500	100	1/2"	1/2"	1/2 Hp
	76	1.1	4.3	1500	100	1/2"	1/2"	1/2 Hp
	92	1.4	5.2	1500	100	1/2"	1/2"	1/2 Hp
	106	1.6	6.2	1500	100	1/2"	1/2"	1/2 Hp
	121	1.9	7.0	1500	100	1/2"	1/2"	1/2 Hp
138	2.1	8.0	1500	100	1/2"	1/2"	1/2 Hp	
KP-15	20	0.7	2.5	1500	100	1/2"	1/2"	3/4 Hp
	31	1.0	3.8	1500	100	1/2"	1/2"	3/4 Hp
	46	1.5	5.6	1500	100	1/2"	1/2"	3/4 Hp
	60	2.0	7.4	1500	100	1/2"	1/2"	3/4 Hp
	76	2.6	10.0	1500	100	1/2"	1/2"	3/4 Hp
	92	3.1	12.0	1500	100	1/2"	1/2"	3/4 Hp
	106	3.7	14.0	1500	100	1/2"	1/2"	3/4 Hp
	121	4.2	16.0	1500	100	1/2"	1/2"	3/4 Hp
	138	4.8	18.0	1500	100	1/2"	1/2"	3/4 Hp

	Liquid End	Plunger	Plunger Packing	Valve Seat	Valve Ball	Valve Guide	Valve Seal
Material	316L SS	SAF 2205	PTFE+Kevlar	316L SS	316L SS	316L SS	FKM



Phone: +1(770)943-4922

1059 Triad Court, Suite 1 - Marietta, GA 30062 USA

E-mail: sales@tkmindustries.com
www.tkmindustries.com
 twitter @tkmpumps
 #keepbusinesspumping